

Terra 124/184 UL

Electric Vehicle Infrastructure



The Terra all-in-one DC fast charger offers power up to 180 kW, with convenient charging times for every EV – including those with HV batteries.

The compact, modular design makes it perfect for retail, highway or fleet use, with power sharing to further optimize utilization. All Terra chargers feature connectivity for remote services and OCPP enablement.

◀ *The Terra 124/184 is available with CCS-only, CCS-dual and CCS+CHAdeMO dual outlets. Cable management options enhance reliability and usability.*

Flexible Configuration

Terra DC Fast chargers with power up to 180 kW are designed for the most compact, reliable and futureproof demands. In addition to a range of power selections, Terra chargers can be configured with CCS and CHAdeMO connector cables, in single or dual outlet format. Cable management, payment enablement and connectivity choices also offer owners, operators and site hosts options tailored to the needs of every charging site, from public to fleet needs.

The Most Reliable, Scalable Choice

ABM's Terra chargers offer redundant power architecture for the highest uptime in the EV infrastructure industry. Additionally, Terra chargers can meet the needs of high voltage BEVs up to

920V, making these systems fully compatible with all current and future EVs. With a host of configuration options, Terra DC fast chargers are ready to support EV market growth over time.

Power Sharing for High Utilization

Enabling every business model is critical for EV charging infrastructure. With this goal in mind, ABM has designed the Terra 124 and Terra 184 models with power sharing technology, which is capable of charging two vehicles at the same time. Simultaneous charging can deliver higher utilization for every charging asset, a major key to public and fleet electrification success.

Terra "all in one" chargers are offered from up to 180 kW.

The Terra 124 and 184 models can charge two vehicles at the same time.



Terra 124
one EV
up to
120 kW



Terra 124
two EVs
each up to
60 kW



Terra 184
one EV
up to
180 kW



Terra 184
two EVs
each up to
90 kW

Key Features

- A compact, all-in-one charger from 60 kW to 180 kW
- Terra 124 and Terra 184 can fast-charge two vehicles at the same time
- Paralleled power module topology with automatic failover offers high uptime through redundancy
- Delivers output power continuously and reliably over its lifetime
- Flexible configurations include CCS-single, CCS-dual and CCS+CHAdeMO-dual outlets
- Up to 920 VDC for every passenger or fleet EV
- Bright, daylight readable touchscreen display with graphic visualization of charging session
- High short circuit current rating
- EMC Class B certified for safe use at fuel stations, retail centers, offices, and residential-adjacent sites
- Design enables ADA compliant installations
- RFID authorization modes
- Always connected, enabling remote services, updates and upgrades
- Robust all-weather powder-coated stainless steel enclosure
- Quick and easy installation as well as serviceability

Optional Features

- Reliable cable management system available as ordered or field upgrade
- High current option can deliver up to 400 A for faster peak charging without liquid cooled cables
- Customizable user interface
- Integrated payment terminal
- Web tools for statistics and PIN access management
- Integration with OCPP networks, payment platforms and energy management
- Autocharge and ISO 15118 enabled

Why Charging Operators and Fleets Prefer ABM

- ABM offers the most advanced, safe and reliable EV infrastructure and grid connected technologies
- ABM Connected Services enable every business and remote services model
- ABM's decade of EV charging experience and close cooperation with EV OEMs, networks and fleets

Specifications	Terra 124	Terra 184
Electrical		
Maximum output power	120 kW or 60 kW x 2	180 kW or 90 kW x 2
AC Input voltage	480Y / 277 VAC +/- 10 % (60 Hz)	
AC input connection	3-phase: L1, L2, L3, GND (no neutral)	
Nominal input current and input power rating	153 A, 128 kVA	230 A, 192 kVA
Recommended upstream circuit breaker(s)	200 A	300 A
Power Factor*	> 0.96	
Current THD*	< 5%	
Short circuit current rating	65 kA	
DC output voltage	CCS-1: 150 - 920 VDC; CHAdeMO: 150 - 500 VDC	
DC output current	CCS1 200 A, CHAdeMO: 200 A Optional CCS1 300 A (nominal) and 400 A (peak) high current cable(s)	
Efficiency*	95%	
Interface and Control		
Charging protocols	CCS1 and CHAdeMO 1.2	
User interface	7" high brightness full color touchscreen display	
RFID system	ISO/IEC 14443A/B, ISO/IEC 15393, FeliCa™ 1, NFC reader mode, Mifare, Calypso, (option: Legic)	
Network connection	GSM/3G/4G modem; 10/100 Base-T Ethernet	
Communication	OCPP 1.6 Core and Smart Charging Profiles; Autocharge	
Supported languages	English (others available on request)	
Environment		
Operating temperature	-35 °C to +55 °C / -31 °F to +131 °F (derating characteristics apply at extreme temperatures)	
Recommended storage	-10 °C to +70 °C / 14 °F to +158 °C (dry environment)	
Protection	IP54, NEMA 3R; indoor and outdoor rated	
Humidity	5% to 95%, non-condensing	
Altitude	2000 m (6560 ft)	
General		
Charge cable	6 m (19.6 ft)	
Dimensions (H x W x D)	1900 x 565 x 880 mm / 74.8 x 22.2 x 34.6 in	
Weight	365 kg / 800 lbs	395 kg / 870 lbs
Compliance and safety	UL 2202, CSA No. 107.1-16; UL 2231-1, UL 2231-2, CSA STD C22.2 No. 107.1; NEC Article 625, EN 61851, EN 62196; CHAdeMO 1.2; DIN 70121, ISO 15118; IEC 61000-6-3; EMC Class B, FCC Part 15	

*Data shown at nominal output power

We reserve the right to make technical changes or modify the contents of this document without prior notice. We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of ABM.



Learn more at abm.com/simplifyEV
or call us at 888.681.1573

©2023 ABM Industries Inc.
All Rights Reserved.
ABM-16064-0223